

Smooth  
Composite - Mineral Fiber + Fiberglass

The Adagio line provides a white, clean, monolithic ceiling visual. Design with other products in the Symphony® f line for more complex acoustical solutions.




**APPLICATIONS**

- Private Offices
- Music Rooms
- Patient Rooms
- Conference Rooms
- Medical Treatment / Exam Rooms
- Other Commercial Buildings / Space Applications

**FEATURES AND BENEFITS**

- Unique composite panel with optimal sound absorption and attenuation
- Fiberglass layer provides exceptional sound absorption and acoustic comfort (0.80-0.90 NRC)
- Offers highly effective sound containment (CAC 36-42)
- Can enhance space privacy compliance (assists with HIPAA requirements in healthcare spaces)
- Certified VOC compliant
- Exceeds FGI guidelines for cleanability and acoustic performance
- Wash tested to 1,000 cycles with no sign of wear

**SUSPENSION SYSTEM OPTIONS**



Trim  
15/16 Grid

Reveal  
15/16 Grid

Narrow Reveal  
9/16 Grid

Narrow Reveal  
9/16 Grid Bolt Slot

**LEED® v4**

RECYCLED CONTENT		15 - 51%
<input checked="" type="checkbox"/>	EA: Optimize Energy Performance	
<input checked="" type="checkbox"/>	EA: Prereq. Min. Energy Performance	
<input checked="" type="checkbox"/>	EQ: Interior Lighting	
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)	
<input checked="" type="checkbox"/>	EQ: Acoustic Performance	
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)	
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials	
<input checked="" type="checkbox"/>	EQ: Daylight	
<input type="checkbox"/>	MR: Material Ingredients (HPDs)	
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials	
<input type="checkbox"/>	MR: Environmental Product Declarations (EPDs)	
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning	

LEED® is a registered trademark of the U.S. Green Building Council.

Smooth  
Composite - Mineral Fiber + Fiberglass

All products in this line feature these attributes:



SAG RESISTANT



BIO SHIELD® MOLD/MILDEW RESISTANT



LR 0.90



WASHABLE W/SANITIZING CHEMICALS



EMISSION COMPLIANT CERTIFIED



RECYCLED CONTENT 15-51%

ADAGIO		Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet	
<b>TRIM</b>											
	NRC 90	1662-IOF-1	Panels	24 x 24 x 1-1/2	0.90	36	15%	8	32	45	20
		1660-IOF-1	Panels	24 x 48 x 1-1/2	0.90	38	15%	4	32	45	16
<b>REVEAL</b>											
	NRC 90	1662B-IOF-1	Panels	24 x 24 x 1-1/2	0.90	36	15%	8	32	45	20
		1660B-IOF-1	Panels	24 x 48 x 1-1/2	0.90	38	15%	4	32	45	16
<b>NARROW REVEAL</b>											
	NRC 90	1662F-IOF-1	Panels	24 x 24 x 1-1/2	0.90	36	15%	8	32	45	20
		1660F-IOF-1	Panels	24 x 48 x 1-1/2	0.90	38	15%	4	32	45	16
<b>ADAGIO HIGH CAC</b>											
<b>TRIM</b>											
	NRC 80	1672-IOF-1	Panels	24 x 24 x 1-1/2	0.80	40	51%	8	32	45	20
		1670-IOF-1	Panels	24 x 48 x 1-1/2	0.80	42	51%	4	32	45	16
<b>REVEAL</b>											
	NRC 80	1672B-IOF-1	Panels	24 x 24 x 1-1/2	0.80	40	51%	8	32	45	20
		1670B-IOF-1	Panels	24 x 48 x 1-1/2	0.80	42	51%	4	32	45	16
<b>NARROW REVEAL</b>											
	NRC 80	1672F-IOF-1	Panels	24 x 24 x 1-1/2	0.80	40	51%	8	32	45	20

All Adagio products are available in metric. Additional sizes available upon request.

**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990

## ACCESSORIES

ADAGIO ACCESSORIES	Product Name	Pieces/carton	Use	
	1400-SEL-1	Fiberglass Edge Sealant	1	For re-sealing cut edges; 1 quart container

## PHYSICAL DATA

### MATERIAL

Composite - Mineral Fiber + Fiberglass

### ASTM E1264 CLASSIFICATION

Type XX, Pattern E

### FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

### MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

### MAINTENANCE

Clean panel using a sponge/cloth dampened with water and mild liquid detergent solution. Do not soak panel. Cleanable with sanitizing chemicals.

### WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/ceilings](http://certainteed.com/ceilings).



## CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM  
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)