

Exceptional performance in high-moisture environments and exterior spaces.




APPLICATIONS

- Parking Garages
- Locker & Shower Rooms
- Pools
- Commercial Kitchens
- Other Commercial Buildings / Space Applications

FEATURES AND BENEFITS

- Paperless, exterior sheathing that is mold and abuse resistant over embedded glass reinforced gypsum (EGRG)
- Sag resistant with exceptional indoor/outdoor performance in applications up to 95% relative humidity
- Vinyl facing cleanable with most sanitizing chemicals
- Wash tested to 2,000+ cycles with no sign of wear
- Clean room component to ISO Class 5
- Satisfies USDA/FSIS guidelines for sanitary applications
- Approved for use in federally registered Canadian food establishments

SUSPENSION SYSTEM OPTIONS



Trim
15/16 Grid

LEED® v4

RECYCLED CONTENT	0%
<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input type="checkbox"/>	EQ: Acoustic Performance
<input type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input type="checkbox"/>	EQ: Low-Emitting Materials
<input checked="" type="checkbox"/>	EQ: Daylight
<input type="checkbox"/>	MR: Material Ingredients (HPDs)
<input type="checkbox"/>	MR: Sourcing Raw Materials
<input type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

Smooth Embedded Glass Reinforced Gypsum

All products in this line feature these attributes:



SAG
RESISTANT



MOLD/
MOISTURE
RESISTANT



LR
0.78



WASHABLE
w/SANITIZING
CHEMICALS

AQUAROCK

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet	
TRIM										
	1182-CRF-1SV	Panels	24 x 24 x 1/2	—	40	0%	8	32	65	44
	1180-CRF-1SV	Panels	24 x 48 x 1/2	—	42	0%	4	32	65	44

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Embedded Glass Reinforced Gypsum

ASTM E1264 CLASSIFICATION

Type XX, Pattern G

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less.

MOLD/MOISTURE RESISTANCE

Moisture- and mold-resistant core.

INSTALLATION CONSIDERATION

Use with environmental suspension system if harsh chemicals or moisture will be present. See Suspension Systems, page 215.

MAINTENANCE

Wash tested to 2,000+ cycles.
Cleanable with sanitizing chemicals.

WARRANTY

10-year 104/95 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/ceilings.



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com