

# SUBMITTAL SHEET

## PLAZA™

Project Name \_\_\_\_\_

Specification Section \_\_\_\_\_

Ceiling Type \_\_\_\_\_

**SUBSTRATE: COMPOSITE  
ALUMINUM HONEYCOMB**

1" (nom.) Panel Height

**SIZES**

(Max. 48" x 120")

- |                                     |                                     |                                     |
|-------------------------------------|-------------------------------------|-------------------------------------|
| <input type="checkbox"/> 24" x 48"  | <input type="checkbox"/> 30" x 30"  | <input type="checkbox"/> 48" x 48"  |
| <input type="checkbox"/> 24" x 60"  | <input type="checkbox"/> 30" x 60"  | <input type="checkbox"/> 48" x 60"  |
| <input type="checkbox"/> 24" x 72"  | <input type="checkbox"/> 30" x 120" | <input type="checkbox"/> 48" x 72"  |
| <input type="checkbox"/> 24" x 96"  |                                     | <input type="checkbox"/> 48" x 96"  |
| <input type="checkbox"/> 24" x 120" |                                     | <input type="checkbox"/> 48" x 120" |

(Contact manufacturer for other sizes.)

**COLOR/FINISH**

- PLAZA White – #5300P  
 Cool Metro Gray – #7000P  
 Other # \_\_\_\_\_

**PERFORATION  
PATTERN**

- #144  
 Non-Perforated

**ACOUSTICAL**

\_\_\_\_\_ (NRC)

**TRIM**

- Extruded Wall Angle  
 Extruded Step Trim  
 3-3/4" J-Trim

Color/Finish \_\_\_\_\_

**CUT-OUTS**

- Square, Size: \_\_\_\_\_  
 Round, Diameter: \_\_\_\_\_

**EXPOSURE**

- Interior


**To Contact Us:**  
5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
phone: 800.366.4327  
fax: 770.806.0214  
CTSpecialtyCeilings.com

**HunterDouglas**   
Ceiling & Wall Products  
exclusively from CertainTeed

**PERFORATIONS**

Perforated panels improve acoustical performance as well as create aesthetic effects.

#144



Perforation dia: .040 in.  
Open area: 6%

**SOUND ABSORPTION (NRC) SUMMARY\***

Sound absorption can be achieved by the addition of backing ceiling panels with acoustical fabric or pad.

Perforation Pattern	% Open Area	Acoustical Infill	NRC
#144	6%	Non-Woven Acoustic	0.80

\* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test Reports available upon request.

**PHYSICAL DATA**

**Substrate:** Composite Aluminum Honeycomb

**Warranty:** 1 year

**Seismic rating:** Zones A,B,C,D,E,F

**Fire rating:** Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

**Weight:** Varies 1.0 - 1.5 lbs./sq.ft.

**Wind load:** N/A

**Recycled content:** Up to 85%

**Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:**

- Cotton White: LR = 0.81