

Textured  
Mineral Fiber

A lightly textured mineral fiber panel with an upscale appearance and effective noise reduction.



**APPLICATIONS**


- Offices
- Healthcare Areas
- Conference Centers
- Retail / Department Stores
- Hospitality Areas
- Other Commercial Buildings / Space Applications



**FEATURES AND BENEFITS**

- Finely textured panel offering an upscale appearance and excellent sound absorption (up to 0.70 NRC)
- Certified VOC compliant
- Cuts cleanly, leading to quicker installation and lower installation costs
- Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product
- Some products available in fire-rated (Protectone) versions
- Available in 6 standard colors for item numbers CM-450, CM-454

**SUSPENSION SYSTEM OPTIONS**



LEED® v4	
RECYCLED CONTENT	
CLASS A PROTECTONE®	70%
	44%

- EA: Optimize Energy Performance
- EA: Prereq. Min. Energy Performance
- EQ: Interior Lighting
- MR: PBT Source Reduction (Healthcare)
- EQ: Acoustic Performance *Applies only to High NRC*
- EQ: Prereq. Min. Acoustic Performance (Schools) *Applies only to High NRC*
- EQ: Low-Emitting Materials
- EQ: Daylight
- MR: Material Ingredients (HPDs)
- MR: Sourcing Raw Materials
- MR: Environmental Product Declarations (EPDs)
- MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.



Textured  
Mineral Fiber

All products in this line feature these attributes:



**CASHMERE HIGH NRC**

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	UL Fire-Rated	LR	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>													
	NRC 70	CM-457NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	63	16
		CM-497NRCP	Panels	24 x 48 x 3/4	0.70	32	70%	—	0.82	8	64	64	16
<b>REVEAL</b>													
	NRC 70	CM-454NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	56	16
		CM-494NRCP	Panels	24 x 48 x 3/4	0.70	32	70%	—	0.82	8	64	64	16
<b>NARROW REVEAL</b>													
	NRC 70	CM-450NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	56	16

**CASHMERE**

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	UL Fire-Rated	LR	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>													
	NRC 60	CM-457	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-497	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
<b>REVEAL</b>													
	NRC 60	CM-454	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-494	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
	NRC 45	PCM-454	Panels	24 x 24 x 3/4	0.45	35	44%	Yes*	0.83	14	56	70	16
<b>NARROW REVEAL</b>													
	NRC 60	CM-450	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-490	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
	NRC 45	PCM-450	Panels	24 x 24 x 3/4	0.45	35	44%	Yes*	0.83	14	56	75	16

\* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column. To specify color other than White, order by item number followed by color code. Example: CM-454 BEB. Color List: Beige Breeze – BEB, Blondewood – BLW, Silver Lining – SIL, Wet Clay – WEC, White Wash – WIW. Only available for CM-454 and CM-450 products.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

**PHYSICAL DATA**

**MATERIAL**  
Mineral Fiber

**ASTM E1264 CLASSIFICATION**  
Type III, Form 2, Pattern C E (High NRC)  
Type III, Form 2, Pattern E

**FIRE CLASS (ASTM E1264)**  
All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

**VOC EMISSIONS**  
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

**MOLD/MILDEW RESISTANCE**  
BioShield treatment included for added mold and mildew resistance.

**INSTALLATION CONSIDERATION**  
Differing manufacturing dates should not be mixed in a single ceiling.

**MAINTENANCE**  
Wipe with a soft cloth or vacuum with brush attachment.

**WARRANTY**  
10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/ceilings](http://certainteed.com/ceilings).



**CertainTeed**

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM  
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)