

## PRODUCT QUALIFICATIONS: BASED ON 2018 FGI GUIDELINE FOR HOSPITALS

	PRICE POINT	NRC	CAC	TYPE	WASHABLE (SOAP & WATER)	WASHABLE (SANITIZING CHEMICALS/ CLEANSERS)	SPECIAL PERFORMANCE CHARACTERISTICS	LOW PARTICLE EMITTER (ISO CLEAN ROOM CLASS COMPONENT)	NON-RESTRICTED AREAS <sup>2</sup>	SEMI-RESTRICTED AREAS	RESTRICTED AREAS <sup>3</sup>	DIETARY & LAUNDRY AREAS	NICU	WAITING AREAS <sup>2,4</sup>
<b>CERTAINTEED QUALIFIED CEILING PANELS<sup>1</sup></b>														
Ecophon® Focus™ <sup>5</sup>	\$\$\$	0.90-0.95	N/A	FG	Yes	No	Available in multiple colors.		R					R
Ecophon Akusto™ Wall Panels (Texona)	\$\$\$\$	0.95	N/A	FG	No	No	Available in multiple colors.		A				R	R
Ecophon Hygiene Advance™ Wall	\$\$\$\$	0.90	N/A	FG	Yes	Yes	Fully-encapsulated impervious to water.	Class 3	A	R	R	R	R	
Ecophon Solo™	\$\$\$\$	0.95	N/A	FG	Yes	No	Available in multiple colors.		A					R
Techstyle® (ceiling/wall panels)	\$\$\$\$	0.90	N/A	FG	No	No	Available in multiple colors, wood grain & patterns.		A					R
Vinylrock / Envirogard™ <sup>7</sup>	\$\$-\$	-	34-36	G	Yes	Yes	Tested to 2000+ Wash Cycles.	Class 5	A	A		R		A
VinylShield™ A & C <sup>7</sup>	\$\$	-	39-42	MF	Yes	Yes	Tested to 2000+ Wash Cycles.	Class 5	A	A		R		A

## SYMPHONY® COLLECTION — A COMPLETE LINE OF ULTRA-DURABLE ACOUSTIC SOLUTIONS WITH A CONSISTENT, SMOOTH FINISH.

Adagio™	\$\$\$	0.90	36-38	C	Yes	Yes	Effective sound absorption with exceptional sound containment.		A	A <sup>8</sup>		A <sup>8</sup>	R	A
Adagio High CAC	\$\$\$	0.80	40-42	C	Yes	Yes	Effective sound absorption with exceptional sound containment.		A	A		A	R	A
Symphony f Rx <sup>5</sup>	\$\$	0.95	25	FG	Yes	Yes	Tested to 2000 Wash Cycles.		A	R <sup>8</sup>		R <sup>8</sup>		R
Symphony m Rx <sup>6</sup>	\$\$	0.75-0.85	35-42	MF	Yes	Yes	Tested to 2000 Wash Cycles.	Class 3	A	R		R		
Symphony f <sup>5</sup>	\$\$	0.90-0.95	N/A	FG	Yes	Yes	Tested to 1000 Wash Cycles.	Class 4	R	R <sup>8</sup>		R <sup>8</sup>		R
Symphony HCAC/HNRC <sup>6</sup>	\$\$	0.75-0.85	33-42	MF	Yes	Yes	Tested to 1000 Wash Cycles.	Class 4	R	R		R		

FOOTNOTES	LEGEND	EXAMPLE AREAS
<p><sup>1</sup>All acoustical ceilings must have a trim edge unless otherwise denoted.</p> <p><sup>2</sup>Panels may have trim, reveal, or narrow reveal edge.</p> <p><sup>3</sup>Restricted areas require a monolithic construction and therefore, suspended ceiling systems are not permitted.</p> <p><sup>4</sup>It is likely that ceiling panels alone will not achieve required acoustics for waiting room. Consider adding wall panels.</p> <p><sup>5</sup>Recommended for use when there are full height wall partitions.</p> <p><sup>6</sup>Recommended for use when there is an open or shared plenum.</p> <p><sup>7</sup>Only use in areas where no noise absorption is required.</p> <p><sup>8</sup>Must be gasketed.</p>	<p><b>Type:</b></p> <p><b>C:</b> Composite</p> <p><b>FG:</b> Fiber Glass</p> <p><b>MF:</b> Mineral Fiber</p> <p><b>G:</b> Gypsum</p> <p><b>Areas:</b></p> <p><b>A:</b> Can be used if desired.</p> <p><b>R:</b> Recommended for use in specified area.</p>	<p>Patient rooms, treatment rooms, pharmacy, central services.</p> <p>Storage areas for clean and sterile supplies, sterile processing rooms, work areas for storage and processing of instruments, scrub sink areas, corridors leading to the restricted areas.</p> <p>Operating rooms, isolation rooms.</p> <p>Dietary facilities, nourishment, clean &amp; soiled (utility/supply/linen).</p> <p>Neonatal Intensive Care Unit.</p> <p>Waiting rooms.</p>

	PRICE POINT	MATERIAL	SURFACE FINISH	SEISMIC RATING	GASKET TYPE	NON-RESTRICTED AREAS	SEMI-RESTRICTED AREAS	RESTRICTED AREAS <sup>3</sup>	DIETARY & LAUNDRY AREAS	NICU	WAITING AREAS
<b>CERTAINTEED QUALIFIED SUSPENSION SYSTEMS</b>											
9/16" EZ Stab Elite Narrow System	\$\$\$	HDG Steel (G30)	Painted Steel	Cat. A-F	N/A	R	R			R	R
15/16" EZ Stab Classic System	\$\$	HDG Steel (G30)	Painted Steel	Cat. A-F	N/A	R	R			R	R
15/16" EZ Stab Cleanroom System	\$\$\$\$	HDG Steel (G60)	Painted Aluminum	Cat. A-F	Closed-Cell (ISO class 3 component)	A <sup>9</sup>	R <sup>9</sup>		R <sup>9</sup>	A <sup>9</sup>	A <sup>9</sup>
15/16" EZ Stab Classic Environmental System	\$\$\$	HDG Steel (G60)	Painted Aluminum	Cat. A-F	N/A	A	R		R	A	A
15/16" EZ Stab Classic Aluminum Capped System	\$\$\$	HDG Steel (G30)	Painted Aluminum	Cat. A-F	N/A	A	R		R	A	A

FOOTNOTES	LEGEND	EXAMPLE AREAS					
<sup>3</sup> Restricted areas ceilings must be "monolithic." Lay-in ceilings of any type are specifically excluded. <sup>9</sup> Use only if acoustical panel weight is less than one pound per sq. ft.	<b>Areas:</b> <b>A:</b> Can be used if desired. <b>R:</b> Recommended for use in specified area.	Patient rooms, treatment rooms, pharmacy, central services.	Storage areas for clean and sterile supplies, sterile processing rooms, work areas for storage and processing of instruments, scrub sink areas, corridors leading to the restricted areas.	Operating rooms, isolation rooms.	Dietary facilities, nourishment, clean & soiled (utility/supply/linen).	Neonatal Intensive Care Unit.	Waiting rooms.

Note: For an atrium or lobby, there are no restrictions as stated in the FGI Guidelines. Please visit our website to see all CertainTeed solutions.

A subsidiary of Saint-Gobain, CertainTeed has shaped the building products industry for more than 110 years. At CertainTeed Architectural, we have the right solution for every space and every budget – from economical acoustical ceiling panels and suspension systems to custom-engineered ceilings showpieces in metal, felt, fiberglass, and wood.

## See our entire line of ceilings & suspension systems at [certainteed.com/architectural](https://certainteed.com/architectural)

This is a quick reference tool. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

