

SUBMITTAL SHEET

HEARTFELT[®]

Project Name _____

Specification Section _____

Ceiling Type _____

PRODUCT

- HeartFelt Linear - HL55 HeartFelt Round - HR64
 HeartFelt Linear - HL80
 HeartFelt Linear - HL105

SUBSTRATE

Felt: Non-woven PES fibers

PROFILE

- HeartFelt Linear: 1-9/16" x 2-3/16" (40mmx55mm)
 1-9/16" x 3-1/8" (40mmx80mm)
 1-9/16" x 4-1/8" (40mmx105mm)

HeartFelt Round: 1-9/16" x 2-1/2" (40mmx55mm)

PANEL COLOR/FINISH

- White - #7593F Black - #7594F Dark Brown - #7578F
 Light Grey - #7596F Creme - #7575F Umber - #7579F
 Medium Grey - #7597F Light Brown - #7576F
 Dark Grey - #7598F Medium Brown - #7577F

SPACING

- 2-3/8" o.c. (60 mm) module, 13/16" reveal
 3-1/8" o.c. (80 mm) module, 1-9/16" reveal
 3-15/16" o.c. (100 mm) module, 2-3/8" reveal
 Other module - Contact manufacturer

PANEL DEPTH

Depth (up to 4-1/8" - 105mm): _____

CARRIERS

- Standard Carrier for HeartFelt - Linear Custom Carrier
 Carrier for HeartFelt - Levels Carrier Color/Finish
 Wave Silver (Standard) - #7178
 Choppy Painted Black - #1863
 Step Other: _____
 Scatter
 Custom _____

 Curved Carrier
 Radius: _____ (Minimum 8')
 Vault
 Valley
 Both

ACOUSTICAL RATING

_____ (NRC)

EXPOSURE

- Interior Only

HeartFelt[®] is a registered trademark of Hunter Douglas, Inc. used with permission.

To Contact Us:

5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
www.CertainTeed.com/Architectural

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

SOUND ABSORPTION (NRC) SUMMARY*

Panel Spacing	Open Area	Reveal	Acoustics
2-3/8" (60 mm)	33%	13/16"	NRC 0.60
3-1/8" (80 mm)	50%	1-9/16"	NRC 0.50
3-15/16" (100 mm)	59%	2-3/8"	NRC 0.45

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: Non-woven PES fibers

Warranty: 1 year limited

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Flame spread: ≤ 25, Smoke ≤ 300

Fire rating: Canada — per CAN/ULC S102.2-10

- Flame spread: = 5, Smoke = 90

Weight: Varies

Wind load: N/A

Light reflectance (LR): Varies with color selected

Given the unique and special nature of our HeartFelt® ceiling product, steps should be taken (before and during installation, as well as over the lifetime of the ceiling) to avoid or minimize static and the accumulation of dust, lint, dirt or airborne particles on or around the felt. Manufacturer does not warrant against or take responsibility for any such static or accumulation.