

# SUBMITTAL SHEET

# HIGH PROFILE SERIES™ HORIZONTALLY CURVED

Project Name \_\_\_\_\_

Specification Section \_\_\_\_\_

Ceiling Type \_\_\_\_\_

## SUBSTRATE

Extruded Aluminum

## PROFILE

(Width x Height)

### Beam

- 1-1/2" x 4-3/8"
- 1-1/2" x 6-3/8"
- 1-1/2" x 8-3/8" (minimum radius 96")
- 2" x 8" (minimum radius 96")
- 4" x 4" (minimum radius 96")

\* Length – minimum 4'-0", maximum 20'-0"

### Aero

- 1-5/8" x 6-3/8"

### Open Beam

- 4" x 4" (minimum radius 96")

**Other** – contact manufacturer

- \_\_\_\_\_

## BEAM SPACING

- 6"
- 8"
- 12"
- Other \_\_\_\_\_

## HORIZONTAL CURVATURE

Radius: \_\_\_\_\_ (Minimum 48", except where otherwise specified)

\* For multiple radii, or two radii on the same beam, contact manufacturer.

## COLOR/FINISH

### Beam Finish

- Cotton White – #0280
- Natural – #7163
- Other \_\_\_\_\_

### Hanger Bracket Finish

- Black
- White
- Painted to match plenum

## END CAPS

- Yes
- No

## EXPOSURE

- Interior Only

### To Contact Us:

5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
phone: 800.366.4327  
fax: 770.806.0214  
CTSpecialtyCeilings.com

**HunterDouglas**   
Ceiling & Wall Products  
exclusively from CertainTeed

# SUBMITTAL SHEET **HIGH PROFILE SERIES™ HORIZONTALLY CURVED**

## **PHYSICAL DATA**

---

**Substrate:** Aluminum

**Warranty:** 1 year

**Seismic rating:** Zones A,B,C,D,E,F

**Fire rating:** Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread:  $\leq 25$ , Smoke  $\leq 50$

**Weight:** Varies 2.0 - 4.0 lbs./sq.ft.

**Wind load:** N/A

**Recycled content:** Minimum of 50%

**Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:**

- Cotton White: LR = 0.81