

# THEATRE® BLACK f

Smooth  
Fiberglass

For theatres, salons or galleries, this fiberglass panel offers exceptional acoustic and aesthetic qualities.




## APPLICATIONS

- Theaters / Galleries
- School Auditoriums
- Darkrooms
- Projection Rooms
- Restaurants
- Commercial Interior Spaces
- Other Commercial Buildings / Space Applications

## FEATURES AND BENEFITS

- Specifically developed to meet acoustical requirements for theater applications
- High humidity and inherent mold resistance are perfect for high volume spaces
- Matte finish provides extremely low surface reflectivity when compared to surface painted panels

## SUSPENSION SYSTEM OPTIONS



Trim  
15/16 Grid

## LEED® v4

RECYCLED CONTENT 33%

<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input checked="" type="checkbox"/>	EQ: Acoustic Performance
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input type="checkbox"/>	EQ: Low-Emitting Materials
<input type="checkbox"/>	EQ: Daylight
<input type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

# THEATRE® BLACK *f*

Smooth  
Fiberglass

All products in this line  
feature these attributes:



SAG  
RESISTANT



MOLD/MILDEW  
RESISTANT  
INHERENT



LR  
0.03



RECYCLED  
CONTENT  
33%

THEATRE BLACK <i>f</i>		Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Weight/ carton	Cartons/ pallet	
<b>TRIM</b>											
	NRC 90	1942-THB-5	Panels	24 x 24 x 1	0.90	—	33%	24	96	34	14
		1940-THB-5	Panels	24 x 48 x 1	0.90	—	33%	12	96	34	14
	NRC 75	1912-THB-5	Panels	24 x 24 x 5/8	0.75	—	33%	32	128	22	18
		1910-THB-5	Panels	24 x 48 x 5/8	0.75	—	33%	16	128	22	18

CAC range of 20-25 achieved with CAC foil backing. CAC Foil Backing is available for the entire Theatre Black *f* line as a special order.

**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990

## PHYSICAL DATA

### MATERIAL

Fiberglass

### ASTM E1264 CLASSIFICATION

Type XII, Form 2, Pattern E

### FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

### MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

### MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

### WARRANTY

10-year 104/95 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/ceilings](http://certainteed.com/ceilings).



## CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)